

Model	Nominal End-Flange Diameter [Inch (mm)]		Max Head - Max Capacity	Motor Output [HP (kW)]	Weight Lbs (kg)
	Inlet	Outlet	[ft. - gpm]		
YD-2500GV	1 (25A)	1 (25A)	37 - 22	1/2 (0.4)*	52lbs. (24kg)
YD-2501GV(F)	1 (25A)	1 (25A)	62 - 32	1 (0.75)	52lbs. (24kg)
YD-2502GV(F)	1 (25A)	1 (25A)	63 - 32	2 (1.5)	77lbs. (35kg)
YD-4002GV(F)	1.5 (40A)	1.5 (40A)	87 - 75	2 (1.5)	79lbs. (36kg)
YD-4003GV(F)	1.5 (40A)	1.5 (40A)	83 - 74	3 (2.2)	85lbs. (39kg)
YD-5003GV(F)	2 (50A)	2 (50A)	94 - 90	3 (2.2)	134lbs.(61kg)
YD-5005GV(F)	2 (50A)	2 (50A)	116 - 95	5 (3.7)	196lbs.(89kg)

GV: Glass Fiber Polyplopyrene

GVF: Carbon Fiber Tefron

***3/4 HP (0.55kW) in the US.**